

What is claimed is:

1. A magnetic anchor remote guidance system comprising:

an engagement member which engages with a body portion
5 in a patient's body;

a magnetic anchor made of a magnetic material,
connected to the engagement member; and

a magnetic anchor guide device which is disposed out
of the patient's body and which produces a magnetic field
10 to power the magnetic anchor;

wherein the body portion engaged by the engagement
member is raised by supplying power to the magnetic anchor
via the magnetic field produced by the magnetic anchor
guide device.

15 2. The magnetic anchor remote guidance system
according to claim 1, wherein the engagement member
comprises a clip.

3. The magnetic anchor remote guidance system
according to claim 1, wherein the engagement member has a
20 fishhook shape.

4. The magnetic anchor remote guidance system
according to claim 1, further comprising a connector for
connecting the magnetic anchor with the engagement member.

5. The magnetic anchor remote guidance system
25 according to claim 1, wherein the connector is extendible

and contractible.

6. The magnetic anchor remote guidance system according to claim 1, wherein the magnetic anchor and the engagement member are interconnected in advance.

5 7. The magnetic anchor remote guidance system according to claim 1, wherein the magnetic anchor guide device comprises:

 a magnetic guide member which produces the magnetic field to power the magnetic anchor made of a magnetic
10 material;

 a two-dimensional moving mechanism which moves the magnetic guide member along a U-shaped frame which is arranged in a specific plane; and

 a unidirectional moving mechanism which relatively
15 moves the U-shaped frame in a direction perpendicular to the plane.

8. The magnetic anchor remote guidance system according to claim 1, wherein the magnetic anchor guide device comprises:

20 a magnetic guide member which produces the magnetic field to power the magnetic anchor made of a magnetic material; and

 an arm member which is supported on a main body which is movable on a surface of placement thereof, the arm being
25 bendable at an articulated joint, so that the magnetic

guide member is movable by adjusting the bending angle of the arm at the articulated joint.

9. The magnetic anchor remote guidance system according to claim 1, wherein the magnetic anchor guide
5 device comprises a plurality of magnetic guide devices in which the magnetic fields produced thereby are independently adjustable, so that the magnetic anchor can be powered by the resultant magnetic field of the magnetic guide devices.